

# 5802S

## **Description:**

Item Name: LCD5802S Monitor

Built-in 5.8Ghz Dual diversity receiver automatically for best reception

Built-in 2CH 5.8Ghz AV output and 1CH AV input

Built-in high performance Li-POLYMER Battery: 2000mAH/7.4V

Work status OSD display : RSSI indication ; Battery indicator;Channel indication

A key to automatic signal search

Support Chinese and English menu

Format: JPEG, AVI

Screen size:7"

Screen type:TFT LCD Screen/long life, LED backlight

Resolution: 800\*480

Brightness: 600cd/m2

View Angle:140/120degree (Horizontal/Vertical)

Size:180mm x 120mm x 50mm(Note:Sunshield height:28mm)

Working Voltage: DC 7~16V

Power Consumption: max 650 mA @12V

Battery charging current : 850mA @12V ( max )

Working temperature: -10°C~+ 65 °C

Connectors:RP-SMA female(outer needle)

Antennas Connectors:RP-SMA male (inner hole)

## **Features:**

Built-in Dual Receiver for best reception

Dual buffered AV outputs

Not affect by 2.4GHz R/C Radios

AV Receiver with Diversity inputs

Small, light weight, durable

5 Bands and total 40 Channels

Built-in battery , easy to carry and outdoor use

A key to automatic signal search,Simple operation

Work status OSD display:Always be aware of the device working condition.

**Notice: It can't receive 2 different channels at the same time**